

PB 49-430

WOMEN'S BLACK SLIP ON SHOE



STYLE SPECIFICATIONS

DESCRIPTION:

Water resistant full grain leather steel toe safety shoe.

Colour: Black

Sizes: 35 - 42

Standards:

AS/NZS 2210.3:2019

EN ISO 20345:2011 ASTM F2413-18

Application: Agriculture / Building & Construction / Manufacturing / Mining & Quarrying / Transport & Storage / Warehousing



FEATURES:

- Water resistant full grain leather.
- COOLstep® lining to absorb moisture and odour for optimum freshness and hygiene.
- COMFORTcushion® Impact Absorption System with PORON® protects the heel and ball of the foot.
- NATUREform® steel toe cap with a wide profile for greater comfort. Specifically designed last to support the unique shape of a female foot.
- Oliver SOFTstride® open cell low density urethane foam built in to the insole for ultimate comfort and contour support.
- Excellent slip resistant sole; SRC slip resistant classification. Anti-static.
- PB's dual density PU/Rubber sole with lightweight shock absorbing PU midsole & hardwearing rubber outsole for superior durability. Resistant to 300 °C surface contact.
- Sole resistant to mineral & organic oils & acids. Cut, split and crack resistant.

COMFORT TECHNOLOGY



COMFORTcushion
Impact Absorption



NATUREform
wide profile Type 1 safety toe cap



Water Resistant
Leather



Steel Safety
Toe Cap



SOFTstride
Contour Comfort Support



Antimicrobial
Technology

SOLING TECHNOLOGY



300°C
Heat Resistant sole (572° F)



Abrasion
Resistant sole



Cut Resistant
sole



Slip Resistant
sole



Sole resistant to
mineral oils and acids



Sole resistant to
organic oils and fats



Antistatic
discharges static build-up

OLIVER FOOTWEAR

Level 5, 163-175 O'riordan Street
Mascot, NSW, 2020

Tel: 1300 747 269
(1300 PIP ANZ)

Email: CS@PIPANZ.COM
www.oliver.com.au



Facebook.com/oliversafetyfootwear



@oliver.boots

PIP
GLOBAL SAFETY

PB 49-432Z

WOMEN'S WHEAT ZIP SIDED BOOT



STYLE SPECIFICATIONS



DESCRIPTION:

Water resistant nubuck leather steel toe safety boot.

Colour: Wheat

Sizes: 35 - 42

Standards:

AS/NZS 2210.3:2019

EN ISO 20345:2011 ASTM F2413-18

REPLACEMENT LACE CODE: L-PW130

Application: Agriculture / Building & Construction / Manufacturing / Mining & Quarrying / Transport & Storage / Warehousing

FEATURES:

- Water resistant nubuck leather.
- COOLstep® lining to absorb moisture and odour for optimum freshness and hygiene.
- HEELguard for added stability and impact protection.
- COMFORTcushion® Impact Absorption System with PORON® protects the heel and ball of the foot.
- NATUREform® steel toe cap with a wide profile for greater comfort.
- Specifically designed last to support the unique shape of a female foot.
- Convenient side zipper for easy donning & doffing.
- Oliver SOFTstride® open cell low density urethane foam built in to the insole for ultimate comfort and contour support.
- Excellent slip resistant sole; SRC slip resistant classification. Anti-static.
- PB's dual density PU/Rubber sole with lightweight shock absorbing PU midsole & hardwearing rubber outsole for superior durability. Resistant to 300 °C surface contact.
- Sole resistant to mineral & organic oils & acids. Cut, split and crack resistant.

COMFORT TECHNOLOGY



COMFORTcushion
Impact Absorption



NATUREform
wide profile Type 1 safety toe cap



Water Resistant
Leather



Steel Safety
Toe Cap



SOFTstride
Contour Comfort Support



Antimicrobial
Technology



HEELguard



Convenient Quick
Release Zipper

SOLING TECHNOLOGY



300°C
Heat Resistant
sole (572° F)



Abrasion
Resistant sole



Cut Resistant
sole



Slip Resistant
sole



Sole resistant to
mineral oils
and acids



Sole resistant to
organic oils
and fats



Antistatic
discharges static
build-up

OLIVER FOOTWEAR

Level 5, 163-175 O'riordan Street
Mascot, NSW, 2020

Tel: 1300 747 269
(1300 PIP ANZ)

Email: CS@PIPANZ.COM
www.oliver.com.au



Facebook.com/oliversafetyfootwear



@oliver.boots

PIP
GLOBAL SAFETY

PB 49-445Z

WOMEN'S BLACK ZIP SIDED BOOT



STYLE SPECIFICATIONS



SIDE ZIPPER

DESCRIPTION:

Water resistant full grain leather steel toe safety boot.

Colour: Black

Sizes: 35 - 42

Standards:

AS/NZS 2210.3:2019

EN ISO 20345:2011 ASTM F2413-18

REPLACEMENT LACE CODE: L-PK130

Application: Agriculture / Building & Construction / Manufacturing / Mining & Quarrying / Transport & Storage / Warehousing

FEATURES:

- Water resistant nubuck leather.
- COOLstep® lining to absorb moisture and odour for optimum freshness and hygiene.
- HEELguard for added stability and impact protection.
- COMFORTcushion® Impact Absorption System with PORON® protects the heel and ball of the foot.
- NATUREform® steel toe cap with a wide profile for greater comfort.
- Specifically designed last to support the unique shape of a female foot.
- Convenient side zipper for easy donning & doffing.
- Oliver SOFTstride® open cell low density urethane foam built in to the insole for ultimate comfort and contour support.
- Excellent slip resistant sole; SRC slip resistant classification. Anti-static.
- PB's dual density PU/Rubber sole with lightweight shock absorbing PU midsole & hardwearing rubber outsole for superior durability. Resistant to 300 °C surface contact.
- Sole resistant to mineral & organic oils & acids. Cut, split and crack resistant.

COMFORT TECHNOLOGY



COMFORTcushion
Impact Absorption



NATUREform
wide profile Type 1 safety toe cap



Water Resistant
Leather



Steel Safety
Toe Cap



SOFTstride
Contour Comfort Support



Antimicrobial
Technology



HEELguard



Convenient Quick
Release Zipper

SOLING TECHNOLOGY



300°C
Heat Resistant
sole (572° F)



Abrasion
Resistant sole



Cut Resistant
sole



Slip Resistant
sole



Sole resistant to
mineral oils
and acids



Sole resistant to
organic oils
and fats



Antistatic
discharges static
build-up

OLIVER FOOTWEAR

Level 5, 163-175 O'riordan Street
Mascot, NSW, 2020

Tel: 1300 747 269
(1300 PIP ANZ)

Email: CS@PIPANZ.COM
www.oliver.com.au

Facebook.com/oliversafetyfootwear

@oliver.boots

PIP
GLOBAL SAFETY

AT 49-450Z

WOMEN'S STONE ZIP SIDED LOW-CUT BOOT



STYLE SPECIFICATIONS



SIDE ZIPPER



DESCRIPTION:

All terrain water resistant nubuck leather steel toe safety boot..

Colour: Stone

Sizes: 35 - 43

Standards:

AS 2210.3:2019

EN ISO 20345:2011, ASTM F2413-18

REPLACEMENT LACE CODE: L-PW130

Application: Agriculture / Building & Construction / Manufacturing / Mining & Quarrying / Transport & Logistics / Storage & Warehousing

FEATURES:

- Water resistant nubuck leather.
- TECtuff® toe bumper to protect against scuffing.
- COOLstep® lining to absorb moisture and odour for optimum freshness and hygiene.
- HEELguard for added stability and impact protection
- COMFORTcushion® Impact Absorption System with PORON® helps protect the heel and ball of your foot.
- NATUREform® steel toe cap with a wide profile for greater comfort.
- Oliver SOFTstride® open cell low density urethane foam built in to the insole for ultimate comfort and contour support.
- Convenient quick release side zipper.
- Excellent slip resistant sole; SRC slip resistant classification. Anti-static.
- PB's dual density PU/Rubber sole with lightweight shock absorbing PU midsole and hard wearing rubber outsole for superior durability. Resistant to 300°C surface contact.
- Deep tread profile, with self cleaning design delivers superior traction in the roughest of terrain.
- Sole resistant to mineral and organic oils and acids. Cut, split and crack resistant.

COMFORT TECHNOLOGY



COMFORTcushion
Impact Absorption



NATUREform
wide profile Type 1 safety toe cap



Water Resistant
Leather



Steel Safety
Toe Cap



SOFTstride
Contour Comfort Support



Antimicrobial
Technology



HEELguard



Convenient Quick
Release Zipper

SOLING TECHNOLOGY



300°C
Heat Resistant
sole (572° F)



Abrasion
Resistant sole



Cut Resistant
sole



Slip Resistant
sole



Sole resistant to
mineral oils
and acids



Sole resistant to
organic oils
and fats



Antistatic
discharges static
build-up

OLIVER FOOTWEAR

Level 5, 163-175 O'riordan Street
Mascot, NSW, 2020

Tel: 1300 747 269
(1300 PIP ANZ)

Email: CS@PIPANZ.COM
www.oliver.com.au



Facebook.com/oliversafetyfootwear



@oliver.boots

PIP
GLOBAL SAFETY