





The GripTek® Heavy Duty sole provides a strong foundation from the ground up. Our RotoFlex #8060 safety boot is equipped with an industrial grade zip for ease of access and SoftCell® technology to ensure a secure and comfortable fit.

- Wheat water-resistant nubuck leather upper safety boot—150mm height
- Seven rows of lacing hardware, including lace locking device
- Laces are manufactured from recycled PET
- Durable, heavy duty zip with industrial grade zip fastener
- Lining made from recycled PET offers moisture wicking and long lasting performance
- Streamlined TPU to guard for added leather protection

INFINERGY\* — E-TPU, a super elastic energy foam that is soft but resilient, providing enhanced cushioning and reducing the impact of every step.

 $\textbf{GRIPTEK}^* \textbf{HD} - \text{biomechanically designed TPU outsole designed for optimum grip and stability}.$ 

- high-abrasion resistance and heat resistant to 140°C
- fuel oil resistant
- highly resistant to hydrolysis and microbial attack

FORTASHIELD — broad fitting, cut-resistant steel to ecap tested to resist a 200 joule impact.

AIRCELL —uniquely constructed zoned airflow footbed is designed with specialised breathing channels to activate ventilation, moisture control and provide full-body cushioned comfort. The footbed is anti-bacterial, washable and breathable.

SOFTCELL\*—the overarching comfort system utilising a combination of specialist materials and the unique biomechanical foot-cradling design to increase stability, balance, comfort and manoeuvrability. Designed to reduce the risk of trips, slips and falls.



UNISEX WHEAT NUBUCK ZIP SIDED 150mm HEIGHT

**HALF SIZES** 7.5-11.5

## GRIPTEK.HD















## **FORTASHIELD**











## CERTIFIED TO:

Standard AS 2210.3:2019 ASTM F2413-18 including EH (Clause 5.6)





Refer to blundstone.com.au for further details of the 30 day comfort guarantee and the manufacturer's warranty.

PU - Polyurethane | TPU - Thermoplastic Polyurethane EVA - Ethel Vinyl Acetate | PUR - Polyurethane & Rubber

AU-8060-0323

